

Werkstoff Ms, Messing



Abb.	Gewinde 1 Zoll	Gewinde 2 Zoll	Dichtform	Bestell-Nr.
①	G 1/2	G 3/4	fld.	15 6287 6320
①	G 1	M38 x 1,5	fld. x kon.	15 6287 9334
①	G 3/4	G 1	fld.	15 6287 6324
①	G 1	G 1 1/4	fld.	15 6287 6328
①	G 1	G 1 1/2	fld.	15 6287 6332
①	G 1	G 2	fld.	15 6287 6336
①	G 1 1/4	M45 x 1,5	fld. x kon.	15 6287 9968
①	G 1 1/4	G 1 1/2	fld.	15 6287 6340
①	G 1 1/4	G 2	fld.	15 6287 6344
①	G 1 1/2	M52 x 1,5	fld. x kon.	15 6287 9336
①	G 1 1/2	G 2	fld.	15 6287 6348
①	G 2	M65 x 2	fld. x kon.	15 6287 9337
①	G 2	G 2 1/2	fld.	15 6287 6352
①	G 2	G 3	fld.	15 6287 6356
①	G 2 1/2	M78 x 2	fld. x kon.	15 6287 9339
①	G 2 1/2	G 3	fld.	15 6287 6362
①	G 3	M90 x 2	fld. x kon.	15 6287 9341
②	G 3	G 4	fld.	15 6287 6366

(223)

Werkstoff Al, Aluminiumlegierung



Abb.	Gewinde 1 Zoll	Gewinde 2 Zoll	Dichtform	Bestell-Nr.
②	G 3	G 4	fld.	15 6287 6368
①	G 3	5 1/2 DIN 11	fld.	15 6287 6372
③	G 4	5 1/2 DIN 11	fld.	15 6287 6374

(224)

Reduzierstück RS

Eigenschaften:

- Verschraubung flachdichtend
- Teil des RS® Baukastensystems

Zulassung/Norm:

- Gewinde G = DIN ISO 228/BSP, NPT = API



①



①



②



②



③



③



④



④



⑤



⑥

Werkstoff SS

Werkstoffkombination: Edelstahl 1.4571, Dichtung: PTFE



Abb.	Gewinde innen Zoll	Gewinde außen Zoll	Dichtform	Bestell-Nr.
①	G 1/2	G 3/4	fld.	15 6287 6378
①	G 3/4	G 1	fld.	15 6287 6384
①	G 1	G 3/4	fld.	15 6287 6388
①	G 1	G 1 1/4	fld.	15 6287 6396
①	G 1	G 1 1/2	fld.	15 6287 6400
①	G 1	G 2	fld.	15 6287 6404
①	G 1 1/4	G 1	fld.	15 6287 6410
①	G 1 1/4	G 1 1/2	fld.	15 6287 6416
①	G 1 1/4	G 2	fld.	15 6287 6420
①	G 1 1/2	G 1	fld.	15 6287 6424
①	G 1 1/2	G 1 1/4	fld.	15 6287 6428
①	G 1 1/2	G 2	fld.	15 6287 6434
①	G 2	G 1	fld.	15 6287 6438
①	G 2	G 1 1/4	fld.	15 6287 6442
①	G 2	G 1 1/2	fld.	15 6287 6446
①	G 2	G 2 1/2	fld.	15 6287 6454
①	G 2	G 3	fld.	15 6287 6458
①	G 2 1/2	G 2	fld.	15 6287 6464
①	G 2 1/2	G 3	fld.	15 6287 6470
①	G 3	G 2	fld.	15 6287 6474
①	G 3	G 2 1/2	fld.	15 6287 6478
①	G 3	G 4	fld.	15 6287 6486
⑤	G 3	5 1/2 DIN 11	fld.	15 6287 9347
①	G 4	G 3	fld.	15 6287 6490
⑤	G 4	5 1/2 DIN 11	fld.	15 6287 6494
⑥	5 1/2 DIN 11	G 2	fld.	15 6287 6498
⑥	5 1/2 DIN 11	G 3	fld.	15 6287 6500
⑥	5 1/2 DIN 11	G 4	fld.	15 6287 6506

(222)

Werkstoff Ms

Werkstoffkombination: Messing,
Dichtung: Vulkollan®/Polyurethan



Abb.	Gewinde innen Zoll	Gewinde außen Zoll	Dichtform	Bestell-Nr.
①	G 1/2	G 1/2	fld.	15 6287 6376
①	G 1/2	G 3/4	fld.	15 6287 6380
①	G 3/4	G 3/4	fld.	15 6287 6382
①	G 3/4	G 1	fld.	15 6287 6386
①	G 1	G 3/4	fld.	15 6287 6390
①	G 1	G 1	fld.	15 6287 6392
①	G 1	1 NPT	fld. x Gew.	15 6287 6394
①	G 1	G 1 1/4	fld.	15 6287 6398
①	G 1	G 1 1/2	fld.	15 6287 6402
①	G 1	G 2	fld.	15 6287 6406
①	1 NPT	G 1	fld. x Gew.	15 6287 6408
①	G 1 1/4	G 1	fld.	15 6287 6412
①	G 1 1/4	G 1 1/4	fld.	15 6287 6414
①	G 1 1/4	G 1 1/2	fld.	15 6287 6418
①	G 1 1/4	G 2	fld.	15 6287 6422
①	G 1 1/2	G 1	fld.	15 6287 6426
①	G 1 1/2	G 1 1/4	fld.	15 6287 6430
①	G 1 1/2	G 1 1/2	fld.	15 6287 6432
①	G 1 1/2	G 2	fld.	15 6287 6436
①	G 2	G 1	fld.	15 6287 6440
①	G 2	G 1 1/4	fld.	15 6287 6444
①	G 2	G 1 1/2	fld.	15 6287 6448
①	G 2	G 2	fld.	15 6287 6450
①	G 2	2 NPT	fld. x Gew.	15 6287 6452
②	G 2	G 2 1/2	fld.	15 6287 6456
①	G 2	G 3	fld.	15 6287 6460
①	2 NPT	G 2	fld. x Gew.	15 6287 6462
②	G 2 1/2	G 2	fld.	15 6287 6466
①	G 2 1/2	G 2 1/2	fld.	15 6287 6468
③	G 2 1/2	G 3	fld.	15 6287 6472
③	G 3	G 2	fld.	15 6287 6476
③	G 3	G 2 1/2	fld.	15 6287 6480
③	G 3	G 3	fld.	15 6287 6482
①	G 3	3 NPT	fld. x Gew.	15 6287 6484
③	G 3	G 4	fld.	15 6287 6488
①	3 NPT	G 3	fld. x Gew.	15 6287 9973
②	G 4	G 3	fld.	15 6287 6492
①	G 4	4 NPT	fld.	15 6287 9351
①	G 4	4 NPT	fld. x Gew.	15 6287 9974
⑥	G 4 NPT	G 4	fld. x Gew.	15 6287 9353
⑥	5 1/2 DIN 11	G 3	fld.	15 6287 6502
⑥	5 1/2 DIN 11	G 4	fld.	15 6287 6508

(223)

Werkstoff Al

Werkstoffkombination: Aluminiumlegierung,
Dichtung: Vulkollan®/Polyurethan



Abb.	Gewinde innen Zoll	Gewinde außen Zoll	Dichtform	Bestell-Nr.
①	G 3	5 1/2 DIN 11	fld.	15 6287 9349
⑥	G 4	5 1/2 DIN 11	fld.	15 6287 6496
⑥	5 1/2 DIN 11	G 3	fld.	15 6287 6504
⑥	5 1/2 DIN 11	G 4	fld.	15 6287 6510

(224)